

MAINTENANCE INSTRUCTIONS COMMERCIAL WALLCOVERING **HUSH**

Commercial Wallcovering product **HUSH** is manufactured with solution dyed polyolefin and polyester staple fibers which inherently resist stains, moisture, mildew, rot and bacteria.

GENERAL

- Acoustical Wallcovering will stay attractive and serviceable with regular vacuuming.
- Carefully blot liquid spills immediately with a dry, white absorbent cloth or paper towel. Avoid scrubbing the area. This may spread the stain or distort pile.
- For solids, allow drying, remove with cloth, gently brush and vacuum.
- Most stains will disappear when treated with a mild detergent.
- To prevent spreading, work from the edges of the stain to the center.
- After the stain has been removed, rinse with a mist sprayer of cold water and blot until dry.
- If you elect to use a cleaning solvent or spot removal agent, test in an inconspicuous area to make certain the solution does not alter color or damage fiber and blot dry.

ADHESIVE

- A clear, non-staining adhesive will help prevent problems if dropped on the face of the material.
- Care should be taken not to get adhesive on the face. If necessary, adhesive can be removed with a damp sponge or allowed to dry, brush and vacuum.
- Instructions from adhesive manufacturer should be strictly followed.

RECOMMENDATIONS

- Immediate attention to any spill will increase the probability of removal.
- Repeating the steps: soak-wipe-rinse-blot dry, may be required to fully extract contaminant.
- For most cleaners, rinse with a mist sprayer of cold water to prevent residue of cleaning solution from attracting future soil.
- For best results, call an experienced, professional textile wall covering or carpet cleaner.