

ONE DRY ERASE SYSTEM

- Versatile & Colourful
- Magnetic
- Dry Erase Writing Walls

MAGNETIC PAINTABLE BASE

- Quick and easy installation.
- Saves time and money.
- Takes less man hours to install.
- 54-inch material is wider than competitors.
- Greater width results in fewer seams and an easier installation.
- Simply overlap and double cut as with any standard commercial wallcovering.
- Paint rolls on evenly and smoothly, hiding any seams.
- Provides strong magnetic hold of papers and documents.

Apply
Magnetic
Wallcovering
to Wall



Apply
Any Colour
Paint Over
Wallcovering



Apply Clear
Dry Erase
Coating

DRY ERASE CLEAR COATING

- Easy installation with one ingredient and no mixing of chemicals.
- Low VOC (virtually no odor) that can be installed in occupied spaces.
- Easy touch ups within a hour of rolling onto the wall.
- Up to 2 hour workingtime/ pot life.
- Unused product can be put back into can and used for up to one year.
- No ghosting.
- 10 year warranty.



odyssey

Odyssey Wallcoverings
THE OBVIOUS CHOICE

One Dry Erase System provides a floor to ceiling dry erase and magnetic receptive wall of any colour. This durable and functional dual component product results in the ultimate tool for collaboration and creativity.



MAGNETIC PAINTABLE BASE

- Quick and easy installation that saves time and money.
- 54-inch material is wider than competitors. This results in fewer seams and an easier installation.
- Simply overlap and double cut as with any standard commercial wallcovering. Paint rolls on evenly and smoothly, hiding any seams.
- Provides strong magnetic hold of papers and documents.

DRY ERASE CLEAR COATING

- Easy installation with one ingredient and no mixing of chemicals.
- Low VOC (virtually no odour) that can be installed in occupied spaces.
- Easy touch ups within a hour of rolling onto the wall.
- Up to two hour working time/potlife.
- Unused product can be put back into can and used for up to one year.
- No ghosting.
- 10 year warranty.

APPLICATION OF MAGNETIC WALLCOVERING

After priming the area, a commercial grade wallcovering adhesive is applied to the wall (dry hang) using a 3/8" nap roller. The 54-inch wide paintable Magnetic Wallcovering Base can be hung either horizontally or vertically depending on your area. We recommend the method that will result in the fewest seams. Seams should be tight fitting to get the desired end result.

APPLICATION OF PAINT (over Wallcovering Base)

The next step is to apply 1 – 2 coats of a high quality FLAT latex Paint + Primer-In-One over the installed Wallcovering Base, tinted to the desired colour. Let the paint cure a FULL 24- hours prior to applying the Clear Dry Erase Coating. Finally, clean with a micro-fiber cloth.

APPLICATION OF CLEAR DRY ERASE COATING

Always stir the product well prior to use and only apply with the provided foam roller cover. With a fully saturated roller, use a vertical up and down coating method. Reload the roller cover and continue down the wall. Repeat until wall is covered, being sure to keep a wet edge at all times. Only one coat is needed.

CARE AND MAINTENANCE

Before Writing on Dry Erase Surface

Wait 5 days after installation before cleaning or writing/erasing on the dry erase surface. After 5 days from completed installation, initially clean the surface with clean water and a soft non-abrasive cloth. Your new dry erase wall will then be ready for use!

Daily Cleaning/Long Term Care

Micro-fiber cloths are recommended as erasers. For cleaning marker residue build-up, use Expo brand dry erase cleaning solution and a soft towel. Do not use abrasive cleaners or tools or pointed writing instruments on the dry erase surface.



SPECIFICATIONS: MAGNETIC RECEPTIVE BASE WALLCOVERING

Total Weight	9.60 oz / lin ft
Total Thickness	16 mil
Width	54 inches
Roll Size	50 ft maximum
Flame Resistance	Class A (ASTM E-84)



CLEAR DRY ERASE COATING

Test	ASTM Method	Result
VOC	D3960	4 g/l
Density	D1475	9.44 lbs/gal
Sag Resistance Crack Resistance	D4400	<3 mils
Elongation	D522	>32%
Gloss 60 Degree	D523	85-90 @ 3 mil coating
QUV/500 Hrs, UVA 340	D4587	Visual Gloss Change - Minimal Visual Colour Change - NONE Other Detrimental Film Effects - NONE DE= 1.40
Flammability	E-84	Flame Speed - 5 Smoke Development - 0
Flashpoint	D92	>200F
Scrub Resistance	D2486	>15,000 Cycles
Washability	D3450	98.8%

ACCESSORIES

TSI - Snap Trim



TSI - Marker Tray



TSI - Cork Trim



Micro-Fiber Erasers



Expo Bold Colour Markers



Expo Spray Cleaner



EASE OF INSTALLATION

ONE Dry Erase System is a typical wallcovering install, followed by painting and then clear coating rolled on as a final step. For detailed instructions, visit odysseywallcoverings.com

EASY TO MAINTAIN

Dry erase markings are removed with a soft cloth or eraser. Expo cleaner can be used for any resistant markings. Surface should be thoroughly cleaned periodically for best performance and appearance. DO NOT USE any abrasive cleaning tools or harsh solvents. Writing surface could be permanently damaged if instructions are not followed.

TEN YEAR WARRANTY

Our Dry Erase products are guaranteed for 10 years from installation date. With proper use and maintenance our product will perform for a minimum of ten years. See detailed cleaning and maintenance instructions for proper care.

CARE AND MAINTENANCE

BEFORE WRITING ON DRY ERASE SURFACE

Before initial use of the writing surface the material must be cleaned with Expo Cleaner and a soft cloth, and then towel dried. Follow with clean water and a soft cloth. Use another clean towel to dry.

MARKERS

We recommend the use of Expo Bold Colour/Original Ink markers.

DAILY CLEANING

Micro-fiber erasers or cloths are recommended to remove dry erase markings. Change or clean the eraser/cloth often to avoid leaving excessive marker residue on the surface. For cleaning marker residue build up, use Expo brand Whiteboard Cleaner and a soft cloth.

Do not use soapy water to clean the surface, as it will leave behind a film that severely interferes with erasing. This is true of any other cleaning agent that leaves a filmy residue behind.

LONG TERM CARE

Clean the entire surface on a regular basis to ensure the ultimate performance and appearance of the product over the long term.

Do not use any abrasive cleaners/cleaning tools, erasers with hard plastic edges/housing or pointed writing instruments on the dry erase surface.